

# **Canada Colors and Chemicals Limited**

152 Kennedy Road South
Brampton, Ontario
Canada
L6W 3G4

General Inquiry Number: (905) 459-1232

# Material Safety Data Sheet Attached

#### **MATERIAL SAFETY DATA SHEET**

This product is distributed by Canada Colors and Chemicals Limited General Inquiry: (905) 459-1232 24 Hour Emergency: (416) 444-2112 CCC: Product Code: \_ 673410 CCC: Product Name: PYRITEMAX 8520

Prince Minerals, Inc. 21 West 46th Street, 14th Floor

New York, New York 10036

**CONTACT NUMBERS:** 

Prince Safety, Health and Environmental:

(646) 747-4176

**CHEMTREC (24-hrs):** (800) 424-9300

Section I: Product Information

Identity: IRON PYRITE

Synonyms: IRON DISULFIDE; FOOL'S GOLD,

PYRITE, FERROUS SULFIDE,

Trade Names: PYRITEMAX

Revision Date: 03/2013

**HMIS** 

Health- 1

Flammability- 0

Reactivity- 0

**Personal Protection:** 







**Section II: Composition** 

 Chemical Name:
 CAS #
 Percent

 Iron Pyrite (FeS2)
 1309-36-0
 100

## **Section III: Health Hazard Data**

Component	CAS	% By	OSHA PEL	OSHA	ACGIH	ACGIH	Listed Carcinogen		
		Wt	(mg/m <sup>3</sup> )	Ceiling	TLV	STEL			
Iron Pyrite	1309-36-0	100	N/A	N/A	N/A	N/A	NTP	IARC	OSHA
							N	N	N

<sup>\*</sup>IARC Group: Not classifiable as carcinogenic to humans

Emergency Overview: Not a fire or spill hazard. Low toxicity- Dry dust is a nuisance particulate. Generally, health effects are provided for exposure to dust that may be generated during product transfer and handling.

Primary Route of Exposure: Inhalation

Relevant Routes of Exposure: EYE CONTACT: Particulate may cause slight to moderate irritation. Abrasive action of dust

particulate can damage eye.

**SKIN CONTACT:** Prolonged or repeated contact may cause slight to moderate irritation. **INHALATION:** Overexposure by inhalation of airborne particulate, dust, or fumes is irritating to the nose, throat, and respiratory tract. Inhalation of excessive levels of dust or fumes may

be harmful.

**INGESTION:** Unlikely route of exposure; no hazard in normal industrial use. Small amounts (< tablespoonful) swallowed during normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. If ingested in sufficient quantity, may cause gastrointestinal disturbances. Symptoms may include irritation, nausea, vomiting,

abdominal pain, and diarrhea.

Acute and Chronic Effects of Exposure: Excessive, short-term exposure to airborne mineral dusts and particulate may cause upper

respiratory and eye irritation.

Excessive, long-term inhalation of airborne mineral dusts and particulate may contribute to the development of bronchitis, reduced breathing capacity, and may lead to the increased susceptibility to lung disease. Long term exposure to high concentrations of dust and fume containing iron compounds is known to produce a condition known as siderosis. On X-rays, it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis producing materials such as silica. Chronic ingestion of excess levels of iron can result in pathological deposition of iron in the body tissues, the symptoms of which are fibrosis of the pancreas, diabetes, mellitus, and liver

cirrhosis.

Signs and Symptoms of Exposure: (Dust) tearing of eyes, burning sensation in the throat, cough, and chest discomfort.

Aggravation of Pre-existing Conditions: The excessive inhalation of mineral dust may aggravate pre-existing chronic lung conditions

such as, but not limited to, bronchitis, emphysema, and asthma.

Not a reproductive hazard.

Section IV: First Aid

**Reproductive Hazards:** 

**Emergency and First Aid Procedures:** EYE CONTACT: Flush eyes immediately with water for at least 15 minutes. Seek medical

attention if irritation persists.

**SKIN CONTACT:** Immediately wash affected area with mild soap and water to remove any dust adhering to the skin. Seek medical attention if irritation develops or persists.

**INHALATION:** If exposed to excessive levels of dust or fumes, remove to fresh air and seek medical attention if cough or other symptoms develop. If not breathing, give artificial

respiration or give oxygen by trained personnel, and get medical attention.

**IF INGESTED:** Unlikely route of exposure. If ingested in sufficient quantity and victim is conscious, give 1-2 glasses of water or milk. Never give anything by mouth to an unconscious person. Leave decision to induce vomiting to qualified medical personnel, since

particles may be aspirated into the lungs. Seek immediate medical attention.

Section V: Fire and Explosion Hazard Data

**Emergency Overview:** Not a fire or spill hazard. Low toxicity; dry dust is a nuisance particulate. Generally,

health effects are provided for exposure to dust that may be generated during product

transfer and handling.

Flammable Properties: This material may ignite combustible materials in the presence of high temperatures.

Extinguishing Media: Exposure of material to water may liberate some sulfur dioxide (SO2) gas. Best to use

dry chemical, CO2 or sand. Use extinguishing media appropriate to combustibles in the

surrounding area.

Protection for Firefighters: Wet material should be kept out of eyes and off skin. As in any fire, wear self-contained

breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

# Section VI: Accidental Release

Containment:	Product is a dry solid (granular or powder) and not readily soluble in water. However, prevent spilled product from entering streams, water bodies, and wastewater systems.					
Cleanup:	Vacuum or sweep up dry material and place in a container for reuse. Avoid creating excessive airborne dust. It is recommended that cleanup personnel wear approved respiratory protection, gloves, long sleeved clothing and goggles to prevent irritation from contact and inhalation.					
Collection:	If possible, collect and reuse spilled product.					
Evacuation:	Isolate hazard area. Keep unnecessary and unprotected personnel from entering area.					
Potential Environmental Effects:	Derived from natural ores; no adverse environmental effects known. However, prevent spilled product from entering streams, water bodies, and wastewater systems					
Section VII: Precautions for Sat	fe Handling and Use					
Handling:	Minimize dust generation and accumulation. Avoid breathing dust. Avoid contact with skin and eyes.					
Storage:	Store in cool, dry area. Keep container closed when not in use.					
Waste Disposal:	If possible, collect and reuse spilled product. Disposal Method: Follow all applicable Federal, State, and local laws, rules, and regulations regarding the proper disposal of this material					
Section VIII: Control Measures/	PPE Requirements					
Engineering Controls:	Minimize dust generation and accumulation. Avoid breathing dust. Keep exposure below the exposure limits listed in Section III.					
Personal Protective Equipment:	Eye Protection: Very irritating to eyes. Wear protective safety goggles when dust generation is likely.  Skin Protection: Wear clothing sufficient to cover the skin, safety shoes, and leather gloves for hand protection against dry material.  Respiratory Protection: Use NIOSH/MSHA approved respiratory protection (air purifying or air supplying) when concentrations are above exposure limit value. A respiratory protection program that meets OSHA 29 CFR part 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator. Use of multi-gas cartridge filter is recommended when hot work is performed in and around material.					
Good Hygienic Practice:	Wash thoroughly after using product. Wash contaminated clothing. Wash hands before eating or drinking.					

## **Section IX: Physical and Chemical Properties**

170 lbs/ft<sup>3</sup> Solid at STP Freeze Point: % volatile by vol: 0% H<sub>2</sub>O **Bulk density:** Water solubility: Slight **Melting Point:** 840 °F Vapor Density: N/A N/A pH: (10% aqueous **Boiling Point:** 6500°F Vapor Pressure: slurry)

Appearance and Odor: A yellowish-green to gray crushed material. Slight odor of SO2

#### Section X: Stability/ Reactivity Data

Stability: Stable under normal conditions of storage.

Conditions to Avoid: None under normal conditions.

Incompatibility (materials to avoid): Acids, and readily combustible materials

Hazardous Decomposition or Byproducts: Exposure to acid may liberate a small amount of hydrogen sulfide

Hazardous Polymerization: Will not occur.

## **Section XI: Toxicological Properties**

 Component
 CAS
 RTECS Toxicity

 Iron Pyrite Ore
 1309-36-0
 LD50/LC50 Not Available

## **Section XII: Ecological Information**

Material derived from mineral ores. No data available on any adverse effects of this material on the environment.

## **Section XIII: Disposal Considerations**

RCRA: As manufactured, this product is not a RCRA listed hazardous waste and does not exhibit any characteristics of a hazardous waste, including TCLP.

Disposal Method: This product is generally suitable for landfill disposal. Follow all applicable Federal, State and local laws regarding proper disposal. If this product has been altered or contaminated with other hazardous materials, appropriate waste analysis may be necessary to determine method of disposal.

## **Section XIV: Transportation Information**

**USDOT: Not regulated** 

Section XV: Regulatory

Page 4 of 5

RCRA: No CERCLA: No SARA: No

TSCA: Not Regulated

#### **Section XVI: Other Information**

Prince Minerals, Inc. provides the information contained herein in good faith, but makes no representation as to its comprehensiveness or accuracy. Such information may be incomplete and/or not applicable to all conditions or situations that may exist or occur. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose or application. Prince Minerals, Inc. assumes no obligation for the information herein and makes NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING (WITHOUT LIMITATION) ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, with respect to the information set forth herein or the suitability of any recommendations made with regard thereto, or the product to which the information refers all of which are AS IS. Accordingly, Prince Minerals, Inc. assumes no liability for any damages, claims or losses arising, directly or indirectly, from any use or reliance upon the information or from any inaccuracy or incompleteness therein. It is solely the responsibility of the user to determine safe conditions for use of this product. Further, the user assumes all liability or expense whatsoever arising out of any improper use thereof.