# **Material Safety Data Sheet**

**EC** LAB

SOLID POWER XL

## 1. Product and company identification

Trade name of product : SOLID POWER XL

Product use : Machine Warewashing Detergent

Product dilution information: Up to 2 oz/10 gal in water

Supplier's information : Ecolab Inc. Institutional Division

370 N. Wabasha Street St. Paul, MN 55102 1-800-352-5326

**Code** : 913472

Date of issue : 21-March-2011

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

### 2. Hazards identification

**Product AS SOLD** 

Physical state : Cast Solid Emergency : DANGER!

overview

CAUSES DIGESTIVE TRACT, EYE AND SKIN

BURNS.

MAY BE HARMFUL IF SWALLOWED.

Do not ingest. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

Potential acute health effects

**Product AS SOLD** 

**Eyes** : Corrosive to eyes.

**Skin** : Corrosive to the skin.

**Inhalation**: No known significant effects or critical hazards.

**Ingestion**: Causes burns to mouth, throat and stomach. May be

harmful if swallowed.

**Product AT USE DILUTION** 

Liquid. CAUTION!

No specific hazard.

No specific hazard.

**Product AT USE DILUTION** 

No known significant effects or critical

hazards.

### See toxicological information (section 11)

## 3. Composition/information on ingredients

### **Product AS SOLD**

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
SODIUM HYDROXIDE	1310-73-2	65
SODIUM CARBONATE	497-19-8	5 - 20
2-propenoic acid, polymer with 2,5-furandione, sodium salt	52255-49-9	1 - 5

#### **Product AT USE DILUTION**

Within the present knowledge of the supplier, this product does not contain any hazardous ingredients in quantities requiring reporting, in accordance with local regulations.

SOLID POWER XL 21 March 2011

### 4. First aid measures

**Product AS SOLD** 

**Eye contact** : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue

flushing with plenty of water for at least 15 minutes.

Get medical attention immediately.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical

attention immediately. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation : No special measures required. Treat symptomatically. No special measures required. Treat

**Ingestion**: If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

### **Product AT USE DILUTION**

No known effect after eye contact. Rinse with water for a few minutes.

No known effect after skin contact. Rinse with water for a few minutes.

No special measures required. Treat symptomatically.

Get medical attention if symptoms occur.

## 5. Fire-fighting measures

**Product AS SOLD** 

Skin contact

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides

Fire-fighting media and instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff.

No specific fire or explosion hazard.

Special protective equipment

for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

required.

mode.

### 6. Accidental release measures

Personal precautions

**Product AS SOLD** 

 Initiate company's spill response procedures immediately. Keep people out of area. Put on appropriate personal protective equipment (see section 8). Do not touch or walk through spilled

material.

Environmental precautions

: Avoid contact of spilled material and runoff with soil

and surface waterways.

Avoid contact of large amounts of spilled material and runoff with soil and surface waterways.

Use personal protective equipment as

Methods for cleaning up

: Collect spillage. Use a water rinse for final clean-up.

Use a water rinse for final clean-up.

## 7. Handling and storage

Handling

Product AS SOLD

: Do not ingest. Do not get in eyes, on skin, or on

clothing. Do not breathe dust. Keep container closed. Use only with adequate ventilation. Wash thoroughly

after handling.

**Storage** : Keep out of reach of children. Keep container tightly

closed.

**Product AT USE DILUTION** 

**Product AT USE DILUTION** 

Wash thoroughly after handling.

Keep out of reach of children.

SOLID POWER XL 21 March 2011

#### Handling and storage 7.

Store between the following temperatures: -10 and

#### 8. **Exposure controls/personal protection**

**Product AS SOLD** 

Engineering measures

: Good general ventilation should be sufficient to control

worker exposure to airborne contaminants.

**Product AT USE DILUTION** 

Good general ventilation should be sufficient

to control worker exposure to airborne

contaminants.

**Personal protection** 

: Due to the form and packaging of the product, no **Eves** protective equipment is needed under normal use

conditions.

: Due to the form and packaging of the product, no Hands

protective equipment is needed under normal use

conditions.

Skin : Due to the form and packaging of the product, no

protective equipment is needed under normal use

Respiratory : Due to the form and packaging of the product, no

protective equipment is needed under normal use

conditions.

No protective equipment is needed under normal use conditions.

No protective equipment is needed under normal use conditions.

No protective equipment is needed under normal use conditions.

No special protection is required.

Ingredient	Exposure limits
SODIUM HYDROXIDE	ACGIH TLV (United States, 2/2010). C: 2 mg/m³ OSHA PEL (United States, 6/2010). TWA: 2 mg/m³ 8 hour(s).

#### Physical and chemical properties 9.

**Product AS SOLD** 

Physical state : Cast Solid Flash point : > 100°C Color : White Odor : Odorless

Hq : 12.5 [Conc. (% w/w): 1%] Product AT USE DILUTION

Liquid. > 100°C Clear Odorless 11.64 to 12.1

#### Stability and reactivity 10.

**Product AS SOLD** 

**Stability** The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.

: Extremely reactive or incompatible with the following materials: acids. Reactivity Highly reactive or incompatible with the following materials: metals.

Reactive or incompatible with the following materials: organic materials.

**Hazardous decomposition** products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

SOLID POWER XL 21 March 2011

### 11. Toxicological information

Potential acute health effects

**Product AS SOLD** 

**Eyes**: Corrosive to eyes.

**Skin**: Corrosive to the skin.

**Inhalation**: No known significant effects or critical hazards.

**Ingestion**: Causes burns to mouth, throat and stomach. May be

harmful if swallowed.

**Product AT USE DILUTION** 

No known significant effects or critical

hazards.

Product AS SOLD
Other adverse effects

Target organs : Contains material which may cause damage to the following organs: lungs, upper

respiratory tract.

12. Ecological information

**Ecotoxicity**: Not reported

## 13. Disposal considerations

**Product AS SOLD** 

**Waste disposal**: Avoid disposal. Attempt to use product completely in

accordance with intended use. Disposal should be in accordance with applicable regional, national and local

laws and regulations.

**Product AT USE DILUTION** 

**Product AT USE DILUTION** 

Not regulated.

Diluted product can be flushed to sanitary sewer. Discard empty container in trash.

### 14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

**Product AS SOLD** 

DOT Classification UN1823

**DOT Proper shipping name** Sodium hydroxide, solid

Class 8
Packing group II

For transport in bulk or using IMDG regulations, see shipping documents for specific transportation information.

**Product AT USE DILUTION** 

Not intended for transport.

## 15. Regulatory information

**Product AS SOLD** 

HCS : Corrosive material Classification Target organ effects

**Product AS SOLD** 

**U.S. Federal regulations** 

**TSCA 8(b) inventory** : All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No listed substance SARA 302/304 emergency planning and notification: No listed substance

SARA 313 Product name CAS number Concentration

4/5

SOLID POWER XL 21 March 2011

## 15. Regulatory information

Form R - Reporting

: No listed substance


requirements

<u>California Prop. 65</u> : No listed substance

### 16. Other information


**Product AS SOLD** 

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)





Date of issue : 21-March-2011
Responsible name : Regulatory Affairs

1-800-352-5326

### Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.